

Pipeline Cleaning Pigs

Standard Red Series 5-8 lb/ft³ (80-128 kg/m³) – Medium Density foam and tough red coating yields a strong resistance to wear yet remains flexible. The 5A, 1A and 1C may be used in pipelines with minor cross sectional diameter reductions or restrictions. (Please consult a qualified representative before applying a 1B, 1D or 4A where line reductions are present.)




5A Red Bare Squeegee Polly Pig (RBS)

The Red Bare Squeegee is the basic Polly-Pig. It is manufactured using a highly flexible, tear-resistant 5-pound per cubic foot density, open-cell polyurethane foam. The base is coated with a tough polyurethane elastomer.



1A Red Plain Spiral Polly Pig (RPS)

The Red Plain Spiral Polly Pig is used for short runs in pipe where some extra abrasion resistance is required. The tough elastomer coating is still flexible enough to allow the pig to reduce to pass through minor cross-sectional diameter reductions or restrictions.




1B Red Spiral Silicone Carbide Polly Pig (RSSC)

The Red Spiral Silicone Carbide Polly Pig is used for short length runs in pipes where an abrasive substance is required to remove deposits on the pipe wall. The pig is capable of turning at elbows, wyes and tees in the line, but caution should be taken before running this pig in a line with restrictions or reductions in diameter.




1C Red Criss Cross Polly Pig (RCC)

The Red Criss Cross Polly Pig is used for medium length runs in pipes where extra abrasion resistance is required. The tough elastomer coating is still flexible enough to allow the pig to reduce to pass through minor cross-sectional diameter reductions or restrictions.



1D Red Criss Cross Silicone Carbide Polly Pig (RCC-SC)

The Red Criss Cross Silicone Carbide Polly Pig is used for medium length runs in pipes where an abrasive substance is required to remove deposits on the pipe wall. The pig is capable of turning at elbows, wyes and tees in the line, but caution should be taken before running this pig in a line with restrictions or reductions in diameter.



4A Red Criss Cross Wire Brush Polly Pig (RCC-WB)

The Red Criss Cross Wire Brush Polly Pig is used for medium length runs in pipes where an abrasive substance is required to remove deposits on the pipe wall. The pig is capable of turning at elbows, wyes and tees in the line, but caution should be taken before running this pig in a line with restrictions or reductions in diameter.